

Count	Description
1	<p data-bbox="225 338 438 360">NBS 050-135/11.30</p>  <p data-bbox="619 636 1061 658">Product photo could vary from the actual product</p> <p data-bbox="225 669 486 692">Product No.: 92559930</p> <p data-bbox="225 757 1428 808">The pumps are non-self-priming, single-stage, centrifugal volute pumps with axial inlet port, radial outlet port and horizontal shaft.</p> <p data-bbox="225 817 1380 869">The pump has a back pull-out design enabling removal of the motor, motor stool, cover and impeller without disturbing the pump housing or pipework.</p> <p data-bbox="225 878 1388 900">All pumps are according to ISO 5199 standards, adjusted for American dimensions on pump and its flanges.</p> <p data-bbox="225 936 1417 987">Inlet and outlet flanges are according to ASME 16.1/16.42. Dimensions and rated performance are according to 175/363 PSI (12/25 bar).</p> <p data-bbox="225 1023 938 1046">The mechanical shaft seal has dimensions according to EN 12756.</p> <p data-bbox="225 1081 1372 1133">Motors are with main dimensions to NEMA standards. The pumps can be equipped with an MLE motor with integrated frequency converter or connected to a Grundfos CUE external frequency converter.</p>



Company name:



Created by:

Phone:

Date:

1/2/2022

92559930 NBS 050-135/11.30 AASG6S5ESBQQESX4 60 Hz





Company name:

Created by:

Phone:

Date:

1/2/2022


Description

Value

Country of origin:

US

92559930 NBS 050-135/11.30 AASG6S5ESBQQESX4 60 Hz



Note! All units are in [in] unless otherwise stated.
 Disclaimer: This simplified dimensional drawing does not show all details.