

Count	Description
1	<p data-bbox="225 338 443 367">NBS 050-150/16.14</p>  <p data-bbox="619 638 1061 663">Product photo could vary from the actual product</p> <p data-bbox="225 672 488 696">Product No.: 92560228</p> <p data-bbox="225 757 1428 808">The pumps are non-self-priming, single-stage, centrifugal volute pumps with axial inlet port, radial outlet port and horizontal shaft.</p> <p data-bbox="225 817 1377 869">The pump has a back pull-out design enabling removal of the motor, motor stool, cover and impeller without disturbing the pump housing or pipework.</p> <p data-bbox="225 878 1385 902">All pumps are according to ISO 5199 standards, adjusted for American dimensions on pump and its flanges.</p> <p data-bbox="225 934 1417 985">Inlet and outlet flanges are according to ASME 16.1/16.42. Dimensions and rated performance are according to 175/363 PSI (12/25 bar).</p> <p data-bbox="225 1016 938 1041">The mechanical shaft seal has dimensions according to EN 12756.</p> <p data-bbox="225 1081 1372 1133">Motors are with main dimensions to NEMA standards. The pumps can be equipped with an MLE motor with integrated frequency converter or connected to a Grundfos CUE external frequency converter.</p>



Company name:



Created by:

Phone:




Date:

12/26/2021

92560228 NBS 050-150/16.14 AASG6S5ESBQQETY6 60 Hz



Description	Value
General information:	
Product name:	NBS 050-150/16.14 AASG6S5ESBQQETY6
Product No.:	92560228
EAN:	5715116270289
Price:	
Technical:	
Rated pump speed:	1185 rpm
Rated flow:	1440 US gpm
Rated head:	109.3 ft
Actual impeller diameter:	16.1 in
Code for shaft seal:	BQQE
Curve tolerance:	2B HI 14.6:2016
Pump version:	A
Materials:	
Pump housing:	Cast iron
Pump housing:	EN-GJL-250
Pump housing:	ASTM A48-35
Impeller:	Stainless steel
Impeller:	EN 1.4308
Impeller:	AISI 304
Shaft:	Stainless steel
Shaft:	EN 1.4462
Shaft:	SAF 2205
Internal pump house coating:	No coating
Material code:	S5
Code for rubber:	E
Installation:	
t max amb:	104 °F
Maximum operating pressure:	174.05 psi
Type of connection:	ANSI
Size of inlet connection:	DN 150
Size of outlet connection:	DN 125
Pressure rating for connection:	Class 125
Mounting options design code:	B
Support block (Yes/No):	Y
Connect code:	G
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	-13 .. 248 °F
Selected liquid temperature:	68 °F
Density:	62.29 lb/ft ³
Electrical data:	
Motor standard:	NEMA
IE efficiency class:	IE3 / NEMA Premium
Rated power - P2:	60 HP
Main frequency:	60 Hz
Rated voltage:	3 x 230/460 V
Rated current:	138-69 A
Rated speed:	1185 rpm
Number of poles:	6
Enclosure class (IEC 34-5):	TEFC
Mounting designation (IEC 34-7, Code I):	NEMA type C / foot
Others:	
DOE Pump Energy Index CL:	0.00
Net weight:	1750 lb
Gross weight:	1750 lb
Shipping volume:	35.5 ft ³





Company name:

Created by:


Phone:

Date:

12/26/2021

Description	Value
Country of origin:	US

92560228 NBS 050-150/16.14 AASG6S5ESBQQETY6 60 Hz



Note! All units are in [in] unless otherwise stated.
 Disclaimer: This simplified dimensional drawing does not show all details.